


35W 单路输出开关电源

Single Output Switching Power Supply

特征 Features

- 交流输入转换由开关选择
 - 具有过流、短路保护功能
 - 自冷散热
 - 100%满负荷烧机测试
 - 低价位、高可靠性
- Convert AC input selected by switch
 - With the flow, short circuit protection
 - Heat from the cold
 - 100% full load burn-in test
 - Low-cost, high reliability



129*98*38(L*W*H)

▶ 技术参数 Technical parametric

型号 Model	APS02AC-35-5	APS02AC-35-12	APS02AC-35-15	APS02AC-35-24
直流输出压 DC output voltage	5V	12V	15V	24V
输出电压容差 Output voltage	±2%	±1%	±1%	±1%
额定输出电流 Rated output current	7A	3A	2.4A	1.5A
输出电流范围 Output current range	0~7A	0~3A	0~2.4A	0~1.5A
纹波及噪音 Wave and noise	75mVp-p	100mVp-p	100mVp-p	100mVp-p
进线稳定度 Inlet stability	±0.5%	±0.5%	±0.5%	±0.5%
负载稳定度 Load stability	±1%	±0.5%	±0.5%	±0.5%
直流输出功率 DC output power	35W	36W	36W	36W
效率 Efficiency	70%	76%	78%	78%
直流电压可调范围 Adjustable range for DC voltage	+10,-5%	±10%	±10%	±10%
输入电压范围 AC input voltage range	85~132VAC/ 170~264VAC 由开关选择 47~63Hz; 240~370VDC			
输入电流 Input current	0.8A/115VAC 0.45A/230VAC			
冲击电流 AC inrush current	冷启动电流 Cold start current 18A/115V 36A/230V			
漏电流 Leakage current	<2mA/240VAC			
过载保护 Overload protection	105%~150% 关断电流, 自动恢复 Shut off current, automatically restore			
过电压保护 Over voltage protection			
高温保护 High temperature protection			
温度系数 Temperature coefficient	±0.03/°C (0~50°C)			
启动、上升、保持时间 Setup, rise, hold up time	200ms, 100ms, 30ms			
抗震性 Vibration	10~500Hz, 2G 10分钟/周期, X、Y、Z轴各60分钟			
耐压性 Withstand voltage	输入输出间: 1.5KVAC, 输入与外壳: 1.5KVAC, 输出与外壳: 0.5KVAC Input and output internal: 1.5KVAC, input and enclosure: 1.5KVAC, output and enclosure: 0.5KVAC			
隔离电阻 Isolation resistance	输入输出间, 输入与外壳, 输出与外壳: 500VDC/100MΩ Input and output internal, input and enclosure, output and enclosure: 500VDC/100MΩ			
工作温度、湿度 Working temperature and humidity	-10°C~+60°C, 20%~90%RH			
存储温度、湿度 Store temperature and humidity	-20°C~+85°C, 10%~95%RH			
重量 Weight	0.41Kg			

▶ 安装尺寸图 Installation dimensions (mm)

