

40W 单路输出开关电源

Single Output Switching Power Supply

特征 Features

- 全范围交流输入
- 具有过压、过流、短路保护功能
- 自冷散热
- 100%满负荷烧机测试
- 低价位、高可靠性
- Full range AC input
- Over-voltage, over current, short circuit protection
- Heat from the cold
- 100% full load burn-in test
- Low-cost, high reliability



129*98*38 (L*W*H)

▶ 技术参数 Technical parametric

型号 Model	APS02AC-40-5B	APS02AC-40-12B	APS02AC-40-15B	APS02AC-40-24B
直流输出压 DC output voltage	5V	12V	24V	24V
输出电压容差 Output voltage	± 2%	± 1%	± 1%	± 1%
额定输出电流 Rated output current	8A	3.5A	2.8A	1.8A
输出电流范围 Output current range	0~8A	0~3.5A	0~2.8A	0~1.8A
纹波及噪音 Wave and noise	75mVp-p	100mVp-p	100mVp-p	100mVp-p
进线稳定性 Inlet stability	± 0.5%	± 0.5%	± 0.5%	± 0.5%
负载稳定性 Load stability	± 1%	± 0.5%	± 0.5%	± 0.5%
直流输出功率 DC output power	40W	42W	42W	43W
效率 Efficiency	72%	76%	76%	78%
直流电压可调范围 Adjustable range for DC voltage	+10,-5%	± 10%	± 10%	± 10%
输入电压范围 AC input voltage range	85~264VAC 47~63Hz; 120~370VDC			
输入电流 Input current	1.2A/115VAC 0.6A/230VAC			
冲击电流 AC inrush current	冷启动电流 Cold start current 25A/115V 50A/230V			
漏电流 Leakage current	<1mA/240VAC			
过载保护 Overload protection	105%~150% 关断电流, 自动恢复 Shut off current, automatically restore			
过电压保护 Over voltage protection	输出电源的 115~135%			
高温保护 High temperature protection			
温度系数 Temperture coefficient	± 0.03%/°C (0~50°C)			
启动、上升、保持时间 Setup, rise, hold up time	300ms, 50ms, 60ms			
抗震性 Vibration	10~500Hz, 2G 10分钟/ 周期, X、Y、Z轴各60分钟			
耐压性 Withstand voltage	输入输出间: 1.5KVAC 输入与外壳: 1.5KVAC 输出与外壳: 0.5KVAC Input and output internal: 1.5KVAC, input and enclosure: 1.5KVAC, output and enclosure: 0.5KVAC			
隔离电阻 Isolation resistance	输入输出间, 输入与外壳, 输出与外壳: 500VDC/100MΩ Input and output internal, input and enclosure, output and enclosure: 500VDC/100MΩ			
工作温度、湿度 Working temperature and humidity	-10°C~+60°C, 20%~90%RH			
存储温度、湿度 Store temperature and humidity	-20°C~+85°C, 10%~95%RH			
重量 Weight	0.44Kg			

▶ 安装尺寸图 Installation dimensions (mm)

