

# 15W 单路输出开关电源

Single Output Switching Power Supply

## 特征 Features

- 交流输入转换由开关选择
- 具有过流、短路保护功能
- 自冷散热
- 100%满负荷烧机测试
- 低价位、高可靠性
- Convert AC input selected by switch
- With the flow, short circuit protection
- Heat from the cold
- 100% full load burn-in test
- Low-cost, high reliability



99\*97\*36 (L\*W\*H)

## ▶ 技术参数 Technical parametric

型号 Model	APS02AC-15-5	APS02AC-15-12	APS02AC-15-24
直流输出压 DC output voltage	5V	12V	24V
输出电压容差 Output voltage	±2%	±1%	±1%
额定输出电流 Rated output current	3A	1.3A	0.7A
输出电流范围 Output current range	0~3A	0~1.3A	0~0.7A
纹波及噪音 Wave and noise	50mVp-p	50mVp-p	100mVp-p
进线稳定度 Inlet stability	±0.5%	±0.5%	±0.5%
负载稳定度 Load stability	±1%	±0.5%	±0.5%
直流输出功率 DC output power	15W	15.6W	16.8W
效率 Efficiency	65%	68%	72%
直流电压可调范围 Adjustable range for DC voltage	+10,-5%	±10%	±10%
输入电压范围 AC input voltage range	85-132VAC/170-264VAC由开关选择 47-63Hz;240-370VDC		
输入电流 Input current	0.5A/115V 0.25A/230V		
冲击电流 AC inrush current	冷启动电流 Cold start current 15A/115V 30A/230V		
漏电流 Leakage current	<0.5mA/240VAC		
过载保护 Overload protection	105%~150% 关断电流, 自动恢复 Shut off current, automatically restore		
过电压保护 Over voltage protection	.....		
高温保护 High temperature protection	.....		
温度系数 Temperature coefficient	±0.02%/°C(0~50°C)		
启动、上升、保持时间 Setup, rise, hold up time	200ms, 100ms, 30ms		
抗震性 Vibration	10~500Hz, 2G 10分钟/周期, X、Y、Z轴各60分钟		
耐压性 Withstand voltage	输入输出间: 1.5KVAC 输入与外壳: 1.5KVAC 输出与外壳: 0.5KVAC Input and output internal: 1.5KVAC, input and enclosure: 1.5KVAC, output and enclosure: 0.5KVAC		
隔离电阻 Isolation resistance	输入输出间, 输入与外壳, 输出与外壳: 500VDC/100MΩ Input and output internal, input and enclosure, output and enclosure: 500VDC/100MΩ		
工作温度、湿度 Working temperature and humidity	-10°C~+60°C, 20%~90%RH		
存储温度、湿度 Store temperature and humidity	-20°C~+85°C, 10%~95%RH		
重量 Weight	0.3Kg		

## ▶ 安装尺寸图 Installation dimensions (mm)

